## **BA26H**

## Backbar Cooler

## **Product Features**

- EU Energy Class A
- App. 59% more energy efficient than previous BA-range
- Ventilated cooling for fast pull-down and even temperature
- Energy saving variable speed compressor
- Double glazed tempered glass
- · Hinged alu-framed glass doors
- Easy access electronic thermostat
- Adjustable shelves behind each door
- LED interior light
- Lock







Adjustable wire shelves

Electronic thermostat

High-quality back bar with low energy consumption

The BA is our range of high-quality back bars. It has been updated and now uses in average 59% less energy compared to the previous models from the same range. This backbar has ventilated cooling for a short pull-down time to ensure that you can keep up with customer demand for cold beverages. If you need to adjust the temperature this is easily done on the electronic thermostat.

The back bar cooler is made of solid materials and has adjustable chrome shelves with closely-spaced wires, which gives you a high capacity and stability. Furthermore, it has hinged aluminium doors with double glazed tempered glass. This helps save energy, but it also means a great product visibility.

The BA range is also available in a variant with self-closing sliding doors.

Design and Material		
Door No & Type	2 hinged glass doors	
Door Reversible	No	
Tempered glass	Yes	
Shelves No & Type	4 wire shelves chrome	
Shelf Color	Chrome	
Shelf Dimensions	395x328 mm	
Feet / Legs	4 adjustable feet	
Exterior Finish	Black	
Interior Finish	Stucco aluminium	
Interior Light	LED	
Lock	Yes	

Measures and Content			
Total Display Area	m²	0.5	
Temperature Range	°C	+2 to +10	
Climate Class		4	
Gross / Net Weight	kg	69 / 63	
Gross / Net Volume	1	190 / 182	

Cooling and Functions		
Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic
Refrigerant		R600a
Refrigerant Charge	g	70
Thermometer		Yes

Power and Consumption			
Energy Class		А	
Energy Consumption	kWh/24h	1.08	
Annual Energy Cons.	kWh/year	394	
Max Ambient		30°C at 55% RH	
Input Power	W	115	
Voltage / Frequency	V/Hz	220-240/50	
Noise Level	dB(A)	44	

Dimensions		
Internal Dimension (WxDxH)	mm	900 x 418 x 720
External Dimension (WxDxH)	mm	900 x 520 x 870
Packed Dimension (WxDxH)	mm	985 x 575 x 940
40ft Container Load	pcs	96